

## Elcometer 124 Thickness Gauge



Elcometer 124 Thickness Gauge

The Elcometer 124 Thickness Gauge is used to measure the peak-to-valley height of a surface profile moulded in the Elcometer 122 Testex Replica Tape.

- Available in both Metric and Imperial versions
- Quick and easy to use
- Anvil pressure as required in the Standards

### Surface Profile

The degree of profile on the surface affects a coating's overall performance. The height of the profile (measured from the peaks to the troughs) determines aspects such as adhesion, coverage and overall volume of coating used. If the profile is too large the amount of coating required to ensure adequate coverage increases, otherwise there is a danger that the peaks remain uncoated - allowing rust spots to occur. If the profile is too small, there may be an insufficient key to produce adequate adhesion, leading to premature coating failure. Ensuring the correct surface preparation optimises the performance of the coating and material usage.

There are four different methods available for testing surface profile:

- Surface Comparators
- Replica Tape
- Surface Profile Gauges
- Surface Roughness Testers

Can be used in accordance with

- ASTM D 4417-C
- BS 7079-C5
- ISO 8503-5
- NACE RP0287
- US Navy NSI 009-32
- US Navy PPI 63101-000

*Standards in grey have been superceded but are still recognised in some industries.*

SYNTECH

TECHNICAL SPECIFICATION					
Part Number	Description	Range	Dimensions	Weight	Scale Resolution
E124---3M	Elcometer 124 Metric	0.5mm	125 x 95 x 25mm	270g	2µm
E124---3E	Elcometer 124 Imperial	0.2"	4.9 x 3.6 x 1.0"	9.6oz	0.1mil

## Elcometer 122 Testex® Replica Tape



Elcometer 122 Testex® Replica Tape

Elcometer 122 Testex Tape consists of foam with a non-compressible backing. The foam side is rubbed into the surface providing a permanent mould of the peak-to-valley profile, which can then be measured using the Elcometer 124 Thickness Gauge.

Elcometer 122 Testex Tape is available in three profile ranges. It is important that the tape grade chosen is reflective of the profile being measured, as using tape grade below the actual value may provide a “false” reading.

There are 50 tests in each roll.

Test Area Dimensions:  
19 x 54mm (0.75 x 2.13”)

Can be used in accordance with  
 ASTM D 4417-C  
 BS 7079-C5  
 ISO 8503-5  
 NACE RP0287  
 US Navy NSI 009-32  
 US Navy PPI 63101-000

*Standards in grey have been superceded but are still recognised in some industries.*

### Surface Profile

The degree of profile on the surface affects a coating’s overall performance. The height of the profile (measured from the peaks to the troughs) determines aspects such as adhesion, coverage and overall volume of coating used. If the profile is too large the amount of coating required to ensure adequate coverage increases, otherwise there is a danger that the peaks remain uncoated - allowing rust spots to occur. If the profile is too small, there may be an insufficient key to produce adequate adhesion, leading to premature coating failure. Ensuring the correct surface preparation optimises the performance of the coating and material usage.

There are four different methods available for testing surface profile:

- Surface Comparators
- Replica Tape
- Surface Profile Gauges
- Surface Roughness Testers

TECHNICAL SPECIFICATION					
Description	Profile Range	Part Number			
		1 Roll	Pack of 10	Pack of 50	Pack of 100
Elcometer 122 Coarse	20 - 64µm (0.5 - 2.5mils)	E122----B1	E122----B10	E122----B50	E122----B100
Elcometer 122 X-Coarse	38 - 115µm (1.5 - 4.5mils)	E122----C1	E122----C10	E122----C50	E122----C100
Elcometer 122 X-Coarse Plus	116 - 147µm (4.6 - 5.8mils)	E122----F1	E122----F10	E122----F50	E122----F100

## Related Products



Elcometer 224

**Elcometer 224 Digital Surface Profile Gauge with Bluetooth®**  
The Elcometer 224 Digital Surface Profile Gauge provides an accurate way to measure surface profiles in microns and mils. The Elcometer 224 Model T has a large built-in memory which can store up to 50,000 readings in 999 batches and offers Bluetooth® wireless technology for cable free data transfer.



Elcometer 223

**Elcometer 223 Digital Surface Profile Gauge**  
A Digital Surface Profile Gauge which measures the peak-to-valley height of a surface in a similar way to the Elcometer 224.



Elcometer 125

**Elcometer 125 Surface Comparators**  
These extremely durable comparators allow the estimation of surface roughness of either grit and shot blasted surfaces.



Elcometer 127

**Elcometer 127 Keane-Tator Surface Comparators & Magnifier**  
The Elcometer 127 range of Surface Comparators are available in sand, shot or grit surface profiles. Each comparator is supplied with 5 profile grades ranging from 0.5 - 5.5mils.



Elcometer 129

**Elcometer 129 Rubert & Rugotest Surface Comparators**  
The Elcometer 129 Surface Comparators are available in two models: Elcometer 129 Rubert - available in grit and shot versions; Elcometer 129 Rugotest - shot and grit profiles on the same block.

**Local Distributor: Syntech Surface Finishing Specialists**  
PO Box 19341, 12B Saunders Place, Avondale,  
Auckland, NEW ZEALAND  
Phone: +64 9 820 2121  
Fax: +64 9 820 0101  
Email: [sales@syntechnz.com](mailto:sales@syntechnz.com) [www.syntechnz.com](http://www.syntechnz.com)

**ENGLAND**  
Elcometer Limited  
Edge Lane  
Manchester M43 6BU  
Tel: +44 (0)161 371 6000  
Fax: +44 (0)161 371 6010  
e-mail: [sales@elcometer.com](mailto:sales@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

**USA**  
Elcometer Inc  
1893 Rochester Industrial Drive  
Rochester Hills Michigan 48309

Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: [inc@elcometer.com](mailto:inc@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

**ASIA & THE FAR EAST**  
Elcometer (Asia) Pte Ltd  
896 Dunearn Rd  
Sime Darby Centre #3-09  
Singapore 589472,  
Republic of Singapore

Tel: +65 6462 2822  
Fax: +65 6462 2860  
e-mail: [asia@elcometer.com](mailto:asia@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

**BELGIUM**  
Elcometer SA  
Rue Vallée 13  
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10  
Fax: +32 (0)4 374 06 03  
e-mail: [be\\_info@elcometer.be](mailto:be_info@elcometer.be)  
[www.elcometer.be](http://www.elcometer.be)

**NETHERLANDS**  
Elcometer NL  
Newtonlaan 115  
3584 BH Utrecht

Tel: +31 (0)30 210 7005  
Fax: +31 (0)30 210 6666  
e-mail: [nl\\_info@elcometer.com](mailto:nl_info@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

**FRANCE**  
Elcometer Sarl  
97 Route de Chécy  
45430 BOU

Tel: +33 (0)2 38 86 33 44  
Fax: +33 (0)2 38 91 37 66  
e-mail: [fr\\_info@elcometer.fr](mailto:fr_info@elcometer.fr)  
[www.elcometer.fr](http://www.elcometer.fr)

**GERMANY**  
Elcometer Instruments GmbH  
Ulmer Strasse 68  
D-73431 Aalen

Tel: +49 (0)7361 52806 0  
Fax: +49 (0)7361 52806 77  
e-mail: [de\\_info@elcometer.de](mailto:de_info@elcometer.de)  
[www.elcometer.de](http://www.elcometer.de)